

## **GLOBE VALVES Y TYPE 4500LB**

### **PRODUCT FEATURES**

- The valve stem and valve seat can freely rotate and re-positioned
- The torque will be very light
- The greater the pressure the better the sealing
- The flowing angle between the medium and the Type Y Valve is at 55°

### **MATERIALS**

- F304,F316 Body
- Disc Surfacing STL
- Seat Surfacing STL
- XM-19/17-4PH

### **TECHNICAL DATA**

- ASME B16.34/ B16.5
- Class 4500LB
- Available in 2-1/2" ~ 12"
- Temperature Range:  
-20 °F ~ 800 °F
- DWG# 5563779



**FIG. Y965-B**

# GLOBE VALVES Y TYPE - 4500LB

### DIMENSIONS-WEIGHTS

In	2-1/2	3	4	5	6	8	10	12
<b>L</b>	280	310	370	450	480	620	690	800
<b>D</b>	73	89	114	141	168	219	273	324
<b>d</b>	45	58	80	103	124	173	190	230
<b>H</b>	400	450	630	810	920	1000	1200	1600
<b>Wt.Lbs</b>	287	320	353	926	1499	1985	2756	4013



FIG. Y965-B

### MATERIALS LIST

No	Part	Specifications
1	Body	F304
2	Disc	F316+STL
3	Bottom Stem	XM-19+STL
4	Disc Cap	F316
5	Gasket	F316
6	Bonnet	F304
7	Packing Washer	304
8	Packing	304+Gr
9	Packing Sleeve	A182 F6a
10	Packing Gland	1045
11	Eye Bolt	A193 B7
12	Nut	A194 2H
13	Cover	1045
14	Snap Ring	A182 F6a
15	Gasket	A182 F6a
16	Cotter Pin	SS304
17	Upper Stem	17-4PH
18	Bracket	1045
19	Yoke Nut	B584
20	Impact Block	1020
21	Lock Nut	1045
22	Handwheel	WCB

